# Juralco® SunPivot® Outdoor Living System BPIR Declaration

Version: 3-24 v1

### **Designated building product: Class 2**

#### **Declaration**

Juralco Aluminium Building Products Ltd trading as Juralco has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

#### **Product/system**

Name	Juralco® SunPivot® Outdoor Living System
Line	
Identifier	

#### **Description**

The Juralco® SunPivot® Outdoor Living System is ideal for extra outdoor shelter for your home. The high-quality extruded aluminium structure and louvres can be custom powder coated in a colour of your choice. The motorised ceiling louvres when closed form a weatherproof seal. The structure can be added to, with drop-down screens, aluminium sliding screens or sliding Glass doors on any side.

#### **Scope of use**

Juralco® SunPivot® Outdoor Living System

Juralco® SunPivot® opening louvre roofs are a permanent outdoor living system providing weather protection in a range of outdoor areas including patios, decks, extended courtyards, pool areas, cafe and bar courtyards, outdoor shopping areas etc.

Juralco® SunPivot® Outdoor Living system configurations and sizes are affected by Wind Zone restrictions. For clarification refer to Configurations in the installer manual

The SunPivot Outdoor Living System is built from the following sub-systems:

- Louvres. One type only. Pivot pin at one end; designed to provide a more weatherproof seal when closed. Motorised only.
- Posts. These are a two-part post, with inner stainless-steel angles top and bottom. Always situated at the corners. At ground level they can be connected to foundations in a variety of ways including a hidden base plate. A hidden drainage down pipe per post is possible.
- Beams. The Beams contain all the pivots for Louvre rotation and the Motor actuator All these beams are of two types, depending on Wall attachments or corner Posts All beams have a hidden drainage channel to catch rain.
- Drop down Screens. Screens from the SolarZip® range can be completely hidden inside the Frames thus making this a very useable extra all-weather space.
- Sliding Glass Doors. From the Glaslide range of 10, 12 or 15mm Glass panels. Refer to the 'Glaslide Sliding Glass Doors' Manual
- For larger installations, a Multi bay set out is possible.
- LED lighting can be incorporated in the Top Frame.

The Juralco SunPivot® Outdoor Living System is wholly manufactured by Juralco and supplied as a kitset. All to be assembled on site.

#### **Conditions of use**

- Scope This specification details the documents the SunPivot® Outdoor Living System refers to in relation to the New Zealand Building Code, the manufacturer's documents, products used in the System, and requirements in relation to fixing and surface finishes.
- Manufacturer's Documents The Juralco Outdoor Living System manual details all extrusions and components used for the fabrication and SunPivot® installation/fixing of the system. - Manuals are available from Juralco Aluminium Building Products Ltd 48 Bruce McLaren Rd, Henderson, Auckland Phone 09 478 8018 Fax 09 478 7883 Email specify@juralco.co.nz
- Products Only extrusions, components and hardware supplied by or specified by JABP may be used in the SunPivot® Outdoor Living System Stainless Steel components, hardware, fixings all components to 316 grade or 304.
- Surface Finishing Juralco Aluminium Building Products Ltd is a Dulux Registered Applicator site, registration number 2101. JABP uses only Dulux branded powder coating materials - Dulux Duralloy® powder coating systems are suitable for properties greater than 100m from high tide level AAMA 2603 performance. Residential buildings, 3 levels max. Warranty 10 yrs - Dulux Duralloy Plus® powder coating systems are suitable for properties greater than 10m from high tide level. AAMA 2603 performance. Residential and Light commercial buildings, 3 levels max Warranty 15 yrs - Dulux Duratec® powder coating systems are suitable for properties greater than 10m from high tide level AAMA2603 and 2604 performance. All Residential and Commercial buildings. Warranty 25 yrs.
- Installation and Fixing The Juralco Outdoor Living System must only be installed in accordance with the Juralco Outdoor Living SunPivot® SunPivot®

System manual - The system Structure and Footings are based on NZS 3604:2011 and NZS 1170 Appendix D, Wind Zone calculations.

Juralco SunPivot Outdoor Living System - Structural - Post attach to Joists JOR752 Post Bottom Bracket JOR752 Post Bottom Bracket Complies with NZS3604:2011 -Double Boundary Joists

NOTE: Important Installation notes:

- 1 The Project Engineer must ensure the structure can support the appropriate loads
- 2 Substructure shown indicatively only.
- 3 Timber SG8 minimum strength
- 4 All Fixings must be Stainless steel

#### **Relevant building code clauses**

B1 Structure F2

B1/VM1: NZS 1170: 2021, NZS 1664.1:1997; NZS AS 1720.1.2022; NZS 3101:2006; NZS 3404:1997; NZS 4223.3:2016; NZS 3604: 2011

#### **Contributions to compliance**

NZBC Compliance

• The Juralco® SunPivot® Outdoor Living System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code and B1/VM1: NZS 1170: 2021, NZS 1664.1:1997; NZS AS 1720.1.2022; NZS 3101:2006; NZS 3404:1997; NZS 4223.3:2016; NZS 3604: 2011

• Designed and manufactured in New Zealand, Juralco® SunPivot® Louvre Roof Systems have been engineered and tested by independent engineers to comply with NZS3604:2011 wind zone and snow loading calculations.

• Compliance Documents issued by the Ministry of Business, Innovation & Employment

• Juralco has supplied Engineered calculations for the attachment of the Juralco® SunPivot® Outdoor Living System systems to the ground, timber decks, walls, and soffits, all conforming to NZS1170, Appendix D

• While Juralco has calculated the uplift forces involved with differing connections to differing areas and wind zones Juralco can only guarantee the suitability of the Initial connection. All subsequent connections and strengthening to a structure are the clear responsibility of the builder/ installer. The Concrete foundation calculations do however conform to NZS 1170 Appendix D and can be used with safety.

# **Supporting documentation**

The following additional documentation supports the above statements:

Juralco SunPivot® Outdoor Living System	3-24 v1	www.juralco.co.nz/assets/Uploads/resources/S H-SunPivot-Outdoor-Living-System-3-24-v1.pdf
Producer Statement Request	3-24 v1	https://ps1.juralco.co.nz/
Juralco Warranty	3-24 v1	www.juralco.co.nz/assets/Files/Juralco-Warrant y-Sheet-JUN-2021.pdf

For further information supporting Juralco® Outdoor Living System claims refer to our website.

## **Contact details**

Manufacture location	New Zealand
Legal and trading name of manufacturer	Juralco Aluminium Building Products Ltd trading as Juralco
Manufacturer address for service	48 Bruce McLaren Rd, Henderson, Auckland 0612
Manufacturer website	www.juralco.co.nz/
Manufacturer email	specify@juralco.co.nz
Manufacturer phone number	0508 880 088
Manufacturer NZBN	9429037383664

#### **Responsible person**

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm that Juralco® SunPivot® Outdoor Living System is not subject to a warning on ban under <u>s26 of the Building Act</u>.

Signed for and on behalf of Juralco Aluminium Building Products Ltd trading as Juralco:

Andrew White

Andrew White DIRECTOR March 2024

JURALCO ALUMINIUM BUILDING PRODUCTS LTD TRADING AS JURALCO: 48 Bruce Mclaren, Henderson, Auckland, 0612, New Zealand 09 478 8018 | www.juralco.co.nz/